



FARM SERVICE TYRES



FARM SERVICE TYRES



SHAKTI REAR

Features	Benefits
<ul style="list-style-type: none"> • 45° Knife action lugs for better penetration and cleanability • Big rigid shoulder lugs • Cut protected Nylon Breaker and flatter tread 	<ul style="list-style-type: none"> • Improved traction • Farm and haulage design • Long tyre life • Cut resistant/better retreads

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
8.00-18	4	6	191	840	29.4	520@1.65	-	391	-	TR 218A
12.4-24	6	W11	315	1170	34.8	1215@1.75	-	536	-	TR 218A
12.4-24	8	W11	315	1170	34.8	1420@2.35	-	536	-	TR 218A
11.2-28	6	10	280	1215	33.6	1120@1.85	-	563	-	TR 218A
11.2-28	8	10	280	1215	33.6	1305@2.45	-	563	-	TR 218A
12.4-28	6	W11	315	1270	34.8	1285@1.75	-	586	-	TR 218A
12.4-28	8	W11	315	1270	34.8	1510@2.45	-	586	-	TR 218A
12.4-28	12	W11	315	1270	34.8	1910@3.10	-	586	-	TR 218A
12.4-28*	12	W11	315	1270	39.0	1910@3.10	-	586	-	TR 218A
13.6-28	6	W12	345	1315	39.8	1650@2.05	-	601	-	TR 218A
13.6-28	8	W12	345	1315	39.8	1645@2.35	-	601	-	TR 218A
13.6-28	12	W12	345	1315	39.8	2075@2.35	-	601	-	TR 218A
14.9-28	12	W13	385	1380	41.0	2120@2.35	-	632	-	TR 218A
16.9-28	8	W15L	435	1435	41.6	2180@1.75	-	649	-	TR 218A
16.9-28	12	15	435	1435	41.6	2760@2.55	-	649	-	TR 218A
18.4-30	8	W16L	490	1575	40.0	2900@1.75	-	712	-	TR 218A
18.4-30	10	W16L	490	1575	40.0	2700@1.75	-	712	-	TR 218A
18.4-30	14	W16L	490	1575	40.0	3405@2.65	-	712	-	TR 218A
13.6-38	12	W12	345	1570	39.8	2300@2.65	-	733	-	TR 218A
11.2-24	8	W10	280	1115	33.5	1250@2.45	--	513	-	TR218A
14.9-24	6	W13	385	1280	41.0	1550@1.45	-	578	-	TR218A TL
14.9-24	8	W13	385	1280	41.0	1800@1.85	-	578	-	TR218A TL
18.4-28	8	W16L	490	1525	40.0	2350@1.45	-	688	-	TR218A TL
16.9-30	12	W15	435	1485	41.5	2730@2.45	-	674	-	TR 218A
8.3-32	6	W7	211	1195	30.0	920@2.45	-	567	-	TR 218A
18.4-38	8	W16L	480	1775	40.0	2725@1.45	-	813	-	TR218A TL

14.9-24 Shakti Irrigation Tubless Tyre also available



SHAKTI FRONT



Features	Benefits
<ul style="list-style-type: none"> • 3 rib design with pronounced center rib • Chested shoulder rib • Strong nylon casing 	<ul style="list-style-type: none"> • Enhanced steering control • Self cleaning property • Withstands all weather conditions • Longer tread life

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
5.00-15	4	4	140	655	14.9	365@2.85	-	308	-	TR 15
5.50-16	8	4	154	717	15.5	625@5.00	-	338	-	TR 15
6.00-16	8	4.5	165	740	16.4	675@4.80	-	347	-	TR 15
7.50-16	8	5.5	211	815	21.0	875@3.80	-	380	-	TR 15
6.50-20	8	5	180	865	17.6	850@4.10	-	407	-	TR 15
6.50-16	8	4.5	175	765	22.0	630@4.20	-	358	-	TR15

SHAKTI - PT



Features	Benefits
<ul style="list-style-type: none"> • A unique tread, scientifically positioned • Deep tread with heavy padding 	<ul style="list-style-type: none"> • Self cleaning efficiency • Longer tread life

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
5.00-12	4	4	122	550	24.5	220@2.45	-	261	-	TR 13
6.00-12	4	4	152	622	25.5	320@2.05	-	293	-	TR 13



TRACTOR TRAILER



Features	Benefits
<ul style="list-style-type: none"> • Unique tread design combining circumferential groove and transverse slots at shoulder • Cut protective tread compound 	<ul style="list-style-type: none"> • Free rolling characteristics as well • Side slippage eliminated

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
7.50-16	12	5.5	210	815	10.3	1710@6.00	-	380	-	TR 15
7.50-16	14	5.5	210	815	15.2	1865@7.05	-	380	-	TR 15
9.00-16	16	6.5	255	915	21.6	2290@7.35	-	431	16N	TR 76A

TRACTOR TRAILER 707



Features	Benefits
<ul style="list-style-type: none"> • Unique tread design combining circumferential groove and transverse slots at shoulder • Cut protective tread compound 	<ul style="list-style-type: none"> • Free rolling characteristics • Side slippage eliminated

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
7.50-16	16	5.5	215	820	14.6	2000@8.4	-	383	16N	TR 76A
9.00-16	16	6.5	255	915	20.0	2290@7.35	-	431	16N	TR 76A



FARM MUSCLE



Features	Benefits
<ul style="list-style-type: none"> • Radial Construction • Flatter tread profile • Stronger bead and Trash shield 	<ul style="list-style-type: none"> • Greater traction, less slippage • Less tread wear, More floatation • Resist rim chaffing, Protection from foreign objects

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION SINGLE kgs@kgs/sq.cm	STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
12.4 R 28	-	W11	328	1239	45	1450@1.63	569.5	-	T R 218A
320/85 R 28R1	-	W11	322	1274	39	1600@1.63	583	-	T R 218A
340/85 R 28R1	-	W12	340	1286	40	1750@1.63	585	-	T R 218A

Both tube type and tubeless tyres are available