



LIGHT TRUCK TYRES



LIGHT TRUCK TYRES

LIGHT TRUCK TYRES



SUPERLUG



Features	Benefits
<ul style="list-style-type: none"> • Unique tread compound • Special design with scoops at shoulder • Extra strong casing • Aggressive tread pattern 	<ul style="list-style-type: none"> • Cooler running • Excellent mileage • Better road grip • Better safety and more retreads

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
7.00-15	12	5.5F	205	775	16.0	1175@6.30	-	365	-	TR 15
7.00-16	14	5.5F	204	805	17.0	1315@6.90	1160@6.90	381	16M/16N	AB 1582
7.50-16	16	6.0G	212	825	18.0	1580@7.75	1390@7.75	388	16N	AB 1582
8.25-16	16	6.5	229	863	19.0	1845@ 6.70	1755@ 6.70	406	16N	TR 177A

SUPER TRACTION



Features	Benefits
<ul style="list-style-type: none"> • Aggressive tread pattern • Strong casing 	<ul style="list-style-type: none"> • Superior traction • High road contact area enhancing road grip • Designed for all wheel fitment

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
7.00-15	8	5.5F	196	760	15.3	925@4.20	816@4.20	369	-	TR 75A
7.00-16	8	5.5F	198	785	15.3	966@4.20	840@4.20	372	16N	AB 1582
7.00-16	10	5.5F	198	785	15.3	1090@5.25	975@5.25	372	16N	AB 1582
7.50-16	8	6.0G	210	810	15.0	1105@4.25	970@4.25	382	16N	AB 1582
7.50-16	12	6.0G	210	810	15.0	1405@6.30	1240@6.30	382	16N	AB 1582

LIGHT TRUCK TYRES



M - 77



Features	Benefits
<ul style="list-style-type: none"> • Rib lug tread pattern • Aggressive tread design 	<ul style="list-style-type: none"> • All wheel fitment • Better mileage • Excellent traction

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
7.00-15	10	5.5F	205	780	15.2	1050@5.25	925@5.25	367	-	TR 15
7.00-15	12	5.5F	205	780	15.2	1175@6.30	1030@6.30	367	-	TR 15
7.50-16	14	6.0G	213	827	18.0	1495@7.05	1315@7.05	391	16N	AB1582

SUPERMILER



Features	Benefits
<ul style="list-style-type: none"> • 5 rib design pattern • Unique fan like shoulder design 	<ul style="list-style-type: none"> • Good mileage and traction • Better retreadability

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT215/80D14	10	5.5J	211	691	11.0	1125@5.25	-	324	-	TR 13
LT215/80D14	10	5.5J	211	691	11.0	1125@5.25	-	324	-	TUBELESS
6.70-15	8	5.0K	180	718	12.0	820@4.25	-	335	-	TR 15
7.00-15	8	5.5F	200	772	12.5	925@4.25	-	363	-	TR 15
7.00-15	10	5.5F	200	772	12.5	1050@5.25	-	363	-	TR 15
6.50-16	8	4.5F	174	753	12.5	860@4.25	-	355	-	TR 15
7.00-16	10	5.5F	204	797	12.5	1100@5.25	965@5.25	372	16N	AB1582
7.00-16	12	5.5F	204	797	12.5	1215@6.20	1065@6.20	378	16N	AB1582
7.50-16	12	6.0G	207	810	13.0	1405@6.30	1240@6.30	382	16N	AB1582
7.50-16	14	6.0G	207	810	13.0	1495@7.05	1315@7.05	382	16N	AB1582
8.25-16	16	6.5	229	854	14.0	1845@ 6.70	1755@ 6.70	402	16N	TR 177A



HIGHWAY



Features	Benefits
<ul style="list-style-type: none"> • Unique rib tread pattern • Free rolling tread design • Cooler running compound 	<ul style="list-style-type: none"> • Good road grip • Good mileage

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
7.00-15	8	5.5F	200	757	11.2	925@4.20	815@4.20	367	-	TR 15
7.00-16	8	5.5F	200	783	11.2	965@4.20	850@4.20	371	16N	AB1582
7.50-16	8	6.0G	212	810	11.5	1105@4.25	970@4.25	382	16N	AB1582
7.50-16	12	6.0G	212	810	11.5	1405@6.30	1240@6.30	382	16N	AB1582
7.50-16	14	6.0G	215	824	11.5	1495@7.00	1315@7.00	387	16N	AB1582

LCV RADIAL



STEEL MUSCLE

Features	Benefits
<ul style="list-style-type: none"> • 4 rib design • Unique tread compound 	<ul style="list-style-type: none"> • Enhanced mileage and traction • Better road grip

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT 7.00 R15	10	5.5	206	755	12.5	1050@5.60	-	350	-	TR 150



STEEL MUSCLE - L



Features	Benefits
<ul style="list-style-type: none"> • Specially designed tread block • Good retreadability • Specially designed tread compound 	<ul style="list-style-type: none"> • Low heat generation • Excellent traction & gripping • Long wear life

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT 185 R 14	8	5.5J	189	654	10.5	850@4.6	800@4.6	302	-	TR 13
LT 7.00 R 16	10	5.5F	203	778	12.5	1100@5.6	965@5.6	362	16N	TR 15
LT 7.00 R 16	12	5.5	203	778	12.5	1215@6.7	1065@6.7	362	16N	TR 15
LT 7.50 R 16	14	6.0	212	814	12.5	1495@7.40	1315@7.40	375	16N	TR 15
LT185/85 R 16	8	6.0J	185	725	9.5	925@4.58	-	335	-	-

STEEL MUSCLE - R



Features	Benefits
<ul style="list-style-type: none"> • Exclusive highway application • Rib design for excellent resistance to uneven wear 	<ul style="list-style-type: none"> • Good maneuverability • Excellent mileage • Good cornering control

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT 185 R 14	8	5.5	189	654	10.5	850@4.6	800@4.6	302	-	TR 13
LT 7.00 R 16	10	5.5	203	778	12.5	1100@5.6	965@5.6	362	16N	TR 15
LT 7.00 R 16	12	5.5	203	778	12.5	1215@6.7	1065@6.7	362	16N	TR 15



STEEL MUSCLE

Features	Benefits
<ul style="list-style-type: none"> • 4 rib design • Unique tread compound 	<ul style="list-style-type: none"> • Enhanced mileage and traction • Better road grip

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT 7.50 R16	14	6.0	214	815	12.5	1495@7.40	1315@7.40	381	16N	AB1582
LT 7.50 R16	12	6.0	212	814	12.5	1405@6.70	1240@6.70	375	16N	TR 15



ZQT

Features	Benefits
<ul style="list-style-type: none"> • Specially designed tread pattern for even wear • Excellent all-season performance 	<ul style="list-style-type: none"> • Excellent mileage • Enhanced road grip • Smooth and quiet ride

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
195/70 R14	6	6.0J	196	632	10.5	690@2.96	-	292	-	-
235/70 R16	6	7J	236	733	10.3	925@2.45	-	328	-	-
215 R14	112/110P	6J	216	704	12.25	1120@4.6	160@4.6	324	-	-
235/75 R15	105Q	6.5J	235	733	10.75	925@2.45	-	328	-	-
265/70 R16	112Q	8J	272	778	10.75	1120@2.45	-	348	-	-

LIGHT TRUCK TYRES



ZGT



Features	Benefits
<ul style="list-style-type: none"> • Futuristic design • Bold block tread pattern • Sporty looks 	<ul style="list-style-type: none"> • Excellent traction • Quick handling response

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT 195 R 15	8	5.5K	197	697	10.5	950@4.6	-	321	-	TR 13

ZGP



Features	Benefits
<ul style="list-style-type: none"> • Bold block tread pattern • All terrain tread compound 	<ul style="list-style-type: none"> • Excellent even on rugged terrains • Enhanced breaking and stability

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT 235/75 R15	6	6.5J	240	735	12.5	900@3.5	825@3.5	334	-	TR 13



JOGGER - A/T



Features	Benefits
<ul style="list-style-type: none"> • Bold aggressive pattern • Excellent traction • All terrain rugged design 	<ul style="list-style-type: none"> • Excellent ride control • Long life

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
6.50 R 16	8	4.5	185	750	10.5	920@4.85	870@4.85	339	-	-

ZVTS



Features	Benefits
<ul style="list-style-type: none"> • Carcass incorporates supple sidewalls • Deeper tread grooves in an optimised tread design • Tread design features higher sipe density and computerised tread pitch sequence • Premium all-season tread compound 	<ul style="list-style-type: none"> • Supple sidewalls for comfort & reliability • Outstanding traction and responsive braking capability • Optimum traction and a smooth, quiet ride • Special polymer compound provides long-term even tread wear

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
LT 175 R 14	6	5J	180	635	9.5	710@3.86	670@3.86	280	-	-