



MOTOR SPORTS



MOTOR SPORTS



GRAVEL RALLY

ZDM1



Features	Benefits
<ul style="list-style-type: none"> • Asymmetric pattern 	<ul style="list-style-type: none"> • Good straight line traction and cornering stability on dry gravel circuits • Reinforced side walls for puncture resistance

TYRE SIZE	LOAD/SPEED INDEX	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	TREAD WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	REVOLUTION PER MILE @ 100 MILES PER HOUR	TUBE VALVE CODE
195/60 R15	88S	6.00	195	166	618	11.5	871	Tubeless
185/60 R14	82S	5.5	185	164	581	11.5	928	Tubeless

ZWM1



Features	Benefits
<ul style="list-style-type: none"> • Special pattern • Stable blocks 	<ul style="list-style-type: none"> • Large voids for traction in wet mud • Extra grip on slushy terrain

TYRE SIZE	LOAD/SPEED INDEX	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	TREAD WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	REVOLUTION PER MILE @ 100 MILES PER HOUR	TUBE VALVE CODE
205/65 R15	94S	6.00J	201	155	646	11.5	834	Tubeless



ZDM2 L

Features	Benefits
<ul style="list-style-type: none"> Asymmetric pattern Rugged construction Choice of compounds-soft, medium and hard to meet rallying needs 	<ul style="list-style-type: none"> Superior stright line traction and cornering stability on hard, dry gravelly terrain Reinforced side walls for puncture resistance



For left fitment

TYRE SIZE	LOAD/SPEED INDEX	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	TREAD WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	REVOLUTION PER MILE @100 MILES PER HOUR	TUBE VALVE CODE
205/65 R15	94S	6.00J	201	183	646	11.5	834	Tubeless
195/60 R15	88S	6.00	195	167	618	11.5	869	Tubeless
185/70 R13	86S	5.5	188	164	588	11.5	914	Tubeless

ZDM2 R

Features	Benefits
<ul style="list-style-type: none"> Assymmetric pattern Rugged construction Choice of compounds-soft, medium and hard to meet rallying needs 	<ul style="list-style-type: none"> Superior stright line traction and cornering stability on hard, dry gravelly terrain Reinforced side walls for puncture resistance



For right fitment

TYRE SIZE	LOAD/SPEED INDEX	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	TREAD WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	REVOLUTION PER MILE @100 MILES PER HOUR	TUBE VALVE CODE
205/65 R15	94S	6.00J	201	183	646	11.5	834	Tubeless
195/60 R15	88S	6.00	195	167	618	11.5	869	Tubeless
185/70 R13	86S	5.5	188	164	588	11.5	914	Tubeless



ZDM3 L



Features	Benefits
<ul style="list-style-type: none"> • Assymetric pattern • Choice of Hard & Medium Compound 	<ul style="list-style-type: none"> • Good for Loose Pack Gravel • Tyre for every condition

TYRE SIZE	LOAD/SPEED INDEX	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	TREAD WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	REVOLUTION PER MILE @100 MILES PER HOUR	TUBE VALVE CODE
205/65 R 15	94S	6J	206	171	650	11.5	834	Tubeless

ZDM3 R



Features	Benefits
<ul style="list-style-type: none"> • Assymetric pattern • Choice of Hard & Medium Compound 	<ul style="list-style-type: none"> • Good for Loose Pack Gravel • Tyre for every condition

TYRE SIZE	LOAD/SPEED INDEX	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	TREAD WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	REVOLUTION PER MILE @100 MILES PER HOUR	TUBE VALVE CODE
205/65 R 15	94S	6J	206	171	650	11.5	834	Tubeless



ZG 1 L



Features	Benefits
<ul style="list-style-type: none"> • Assymetric pattern • Choice of Hard & Medium Compound 	<ul style="list-style-type: none"> • Good for Hard Pack Gravel • Tyre for every condition

TYRE SIZE	LOAD/SPEED INDEX	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	TREAD WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	REVOLUTION PER MILE @ 100 MILES PER HOUR	TUBE VALVE CODE
205/65 R 15	94S	6J	207	171	645	11.5	834	Tubeless
195/65 R 15	89S	6J	201	166	627	11.2	810	Tubeless
185/65 R 14	82S	5.5J	186	154	576	11.3	928	Tubeless

ZG 1 R



Features	Benefits
<ul style="list-style-type: none"> • Assymetric pattern • Choice of Hard & Medium Compound 	<ul style="list-style-type: none"> • Good for Hard Pack Gravel • Tyre for every condition

TYRE SIZE	LOAD/SPEED INDEX	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	TREAD WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	REVOLUTION PER MILE @ 100 MILES PER HOUR	TUBE VALVE CODE
205/65 R 15	94S	6J	207	171	645	11.5	834	Tubeless
195/65 R 15	89S	6J	201	166	627	11.2	810	Tubeless
185/65 R 14	82S	5.5J	186	154	576	11.3	928	Tubeless



TARMAC RALLY ZTW 1



Features	Benefits
<ul style="list-style-type: none"> • Proven pattern • Durable compound 	<ul style="list-style-type: none"> • Consistent performer on track and road rallies • Extra grip on slushy terrain

TYRE SIZE	LOAD/SPEED INDEX	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	TREAD WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	REVOLUTION PER MILE @ 100 MILES PER HOUR	TUBE VALVE CODE
175/60 R13	77S	5.00	175	154	534	5.5	958	Tubeless

ZTW 2



Features	Benefits
<ul style="list-style-type: none"> • Optimized tread pattern • Traction compound 	<ul style="list-style-type: none"> • Enhanced water channelling • Better grip and wet tracks

TYRE SIZE	LOAD/SPEED INDEX	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	TREAD WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	REVOLUTION PER MILE @ 100 MILES PER HOUR	TUBE VALVE CODE
185/60 R15	84S	5.5	185	178	609	5.5	838	Tubeless
185/55 R14	79S	6.00	185	175	560	5.5	905	Tubeless



ZW3

GO-KART



Features	Benefits
<ul style="list-style-type: none"> • Rain tyre • Directional • CIK Homologated 	<ul style="list-style-type: none"> • Optimized wet grip • Better aqua planing • Excellent water channeling

TYRE SIZE	POSITION	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
80/250-5	FRONT	-	128	257	-	-	-	-	-	-
150/270-5	REAR	-	189	280	-	-	-	-	-	-

ZD1



Features	Benefits
<ul style="list-style-type: none"> • Slick • Sticky compound • Available on CIK Homologated • Hard / Medium compound 	<ul style="list-style-type: none"> • Firm grip • Excellent wear resistance

TYRE SIZE	POSITION	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
80/250-5	FRONT	-	128	257	-	-	-	-	-	-
150/270-5	REAR	-	189	278	-	-	-	-	-	-



MOCROSS



Features	Benefits
<ul style="list-style-type: none"> • Motocross 	<ul style="list-style-type: none"> • Excellent for medium / soft terrain

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
3.00-21	4	1.85	81	705	12	195@2.3	-	-	-	TR 29
100/90-19	57S	2.5	91	672	16	230@2.5	-	319	-	TR 29
4.25-18	4	2.5	107	692	16	300@2.3	-	-	-	TR 29
2.75-18	4	1.85	74	617	5.2	160@2.25	-	292	-	TR29/A29 1 45