



MUV/RCV PASSENGER



MUV/RCV PASSENGER

MUV/RCV PASSENGER



NDMS



Features	Benefits
<ul style="list-style-type: none"> • Non-directional tread pattern • Strong casing 	<ul style="list-style-type: none"> • Good traction on soft and sandy terrain • All wheel fitment

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
7.00-15	8	5.5F	200	765	13.5	925@4.25	-	360	-	TR 15
6.00-16	6	4.5E	167	735	12.5	650@3.15	-	347	-	TR 15
7.00-16	6	5.5F	197	785	13.0	815@3.15	715@3.15	369	16N	TR 15

ROVER



Features	Benefits
<ul style="list-style-type: none"> • Rib lug combination tread pattern 	<ul style="list-style-type: none"> • Combines superior mileage with excellent traction • Aggressive look and good all round performance

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
6.40-15	8	4.5E	166	700	14.5	710@4.20	-	325	-	TR 13
6.00-16	8	4.5E	166	740	13.0	765@4.25	-	350	-	TR 15



SAFARI



Features	Benefits
<ul style="list-style-type: none"> • Unique tread pattern 	<ul style="list-style-type: none"> • Premium traction and mileage

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
6.00-16	6	4.5E	164	738	13.0	650@3.15	-	349	-	TR 15

TWIN TREAD



Features	Benefits
<ul style="list-style-type: none"> • Flat tread • Unique rib width distribution 	<ul style="list-style-type: none"> • Excellent mileage • Higher road contact area

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
5.60-13	6	4.0J	142	602	8.5	385@2.15	-	280	-	TR 13
6.40-13	6	4.5J	167	648	9.0	465@2.15	-	301	-	TR 13
5.20-14	6	3.5J	137	622	8.0	375@2.15	-	289	-	TR 13
5.90-15	6	4.0J	153	672	8.5	460@2.15	-	313	-	TR 13
6.40-15	8	4.5J	167	697	9.0	600@2.85	-	323	-	TR 13
6.00-16	6	4.5E	165	735	9.5	650@3.15	-	347	-	TR 15



ESTATE



Features	Benefits
<ul style="list-style-type: none"> • Rib lug tread pattern • Aggressive all wheel design 	<ul style="list-style-type: none"> • Enhanced traction • Excellent performance

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
F 78-15	4	5.5J	197	706	9.5	565@1.85	-	317	-	TR 13
F 78-15	6	5.5J	197	706	9.5	705@3.10	-	318	-	TR 13
F 78-15	8	5.5J	197	706	9.5	835@4.25	-	319	-	TR 13

SM - 12



Features	Benefits
<ul style="list-style-type: none"> • 5 Rib design for the Ultra light truck category • Siped ribs • Extra strong casing 	<ul style="list-style-type: none"> • Excellent mileage and traction • Improved safety and retreadability

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
4.50-12ULT	8	3.5J	133	543	8.5	415@4.10	-	253	-	TR 13
6.00-14	8	4.5J	170	686	9.8	750@4.25	710@4.15	322	-	TR 13
6.50-14	8	4.5J	180	705	10.3	840@4.35	795@4.25	330	-	TR 13
195/80 D15	8	5.5J	200	705	12.0	850@4.15	775@4.15	325	-	TR 13



LEGEND



Features	Benefits
<ul style="list-style-type: none"> • Premium non-skid depth • Unique rib width • High sipe density • Thick cross overs • Wrap around shoulder design 	<ul style="list-style-type: none"> • Higher mileage • Increased road contact area • Better wet traction • Easy water drainage • Sure grip while cornering

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
5.65-12	6	4.0J	132	528	9.0	275@2.15	-	245	-	TR 13
5.20-14	6	3.5J	137	624	10.0	375@2.15	-	290	-	TR 13
5.90-15	6	4.0J	151	670	11.0	460@2.15	-	312	-	TR 13

SW 99



Features	Benefits
<ul style="list-style-type: none"> • Rib pattern • Optimum sipes 	<ul style="list-style-type: none"> • Good mileage • Low rolling resistance

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
4.50-12	6	3.5J	126	540	8.5	255@2.15	-	255	-	TR 13
5.65-12	4	4J	132	525	8.0	250@1.70	-	244	-	TR 13
6.15-13	6	4.5J	157	582	9.5	385@2.15	-	270	-	TR 13
5.20-14	6	3.5J	132	610	8.5	375@2.15	-	283	-	TR 13

MUV/RCV PASSENGER



ZGP



Features	Benefits
<ul style="list-style-type: none"> • Bold block tread pattern • All terrain tread compound 	<ul style="list-style-type: none"> • Excellent even on rugged terrains • Enhanced breaking and stability

TYRE SIZE	LOAD/SPEED INDEX	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
215/75 R15	100S	6J	215	701	11.0	800@2.45	-	322	-	TR 13

ZGT



Features	Benefits
<ul style="list-style-type: none"> • Futuristic design • Bold block tread pattern • Sporty looks 	<ul style="list-style-type: none"> • Excellent traction • Quick handling response

TYRE SIZE	LOAD/SPEED INDEX	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
195/80 R15	96S	5.5J	197	695	10.8	710@2.45	-	315	-	TR 13
205/70 R15	95S	6	207	670	8.8	690@2.40	-	302	-	TR 13



ZVRL



Features	Benefits
<ul style="list-style-type: none"> • Aggressive block pattern • Computerised tread pitch sequence 	<ul style="list-style-type: none"> • Good for On/Off Conditions • Quieter Ride

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
265 / 70 R 15	112S	8J	272	753	9.6	1060@2.45	-	336	-	TL
185 / 80 R 16	94S	5.0	187	702	11.2	670@3.57	-	327	-	TL
185 / 80 R 15	93S	5.0	189	672	11.0	650@3.57	-	311	-	TL

ZV2K



Features	Benefits
<ul style="list-style-type: none"> • Carcass incorporates supple sidewalls • Deeper tread grooves in an optimised tread design • Tread design features higher sipe Density and computerised tread pitch Sequence • Premium all-season tread compound 	<ul style="list-style-type: none"> • Supple sidewalls for comfort & reliability • Outstanding traction and responsive braking capability • Optimum traction and a smooth, quiet ride • Special polymer compound provides long-term even tread wear

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
205/65 R15	94H	6J	209	647	8.7	670@ 2.45	-	295	-	TR 13
195/60 R15	88T	6J	201	615	8.8	560@ 2.45	-	282	-	TR 13
155/65 R13	73S	4.50	157	532	8.0	365@ 2.45	-	244	-	-
175/70 R13	82T	5.00	177	576	8.8	475@ 2.45	-	261	-	B57357
165/80 R14	85S	4.50	165	620	8.8	515@ 2.45	-	281	-	TR 13
185/65 R14	86H	5.50	189	596	8.8	530@ 2.45	-	272	-	TR 13
205/55 R16	91V	6.50	214	632	8.8	580@ 2.45	-	291	-	TR 13
225/60 R16	98V	6.50	228	676	8.8	750@ 2.45	-	308	-	-



ZVTS - Tubless



Features	Benefits
<ul style="list-style-type: none"> • Carcass incorporates supple sidewalls • Deeper tread grooves in an optimised tread design • Tread design features higher sipe density and computerised tread pitch sequence • Premium all-season tread compound 	<ul style="list-style-type: none"> • Supple sidewalls for comfort & reliability • Outstanding traction and responsive braking capability • Optimum traction and a smooth, quiet ride • Special polymer compound provides long-term even tread wear

TYRE SIZE	LOAD/SPEED INDEX	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
165/80 R13	83T	4.5J	168	594	8.0	487@ 2.45	-	273	-	TR413/TR 418
175/70 R13	82T	5.0J	177	578	8.5	475@ 2.45	-	267	-	TR413/TR 418
185/70 R14	88T	5.5J	190	615	8.5	560@2.45	-	287	-	TR 413/TR 418
155/80 R13	79T	4.5J	159	575	8.8	437@ 2.45	-	266	-	TR413/TR 418
175/65 R14	82T	5.0J	177	584	8.5	475@ 2.45	-	270	-	TR413/TR 418
185/70 R13	86T	5.5J	183	590	8.5	530@ 2.45	-	273	-	TR413/TR 418
175/70 R14	84T	5.0J	178	603	8.5	500@ 2.45	-	279	-	TR413/TR 418
195/70 R14	91H	6.0J	201	629	8.5	615@ 2.45	-	291	-	TR413/TR 418
185/60 R13	84H	5.5J	189	568	8.3	500@ 2.45	-	263	-	TR413/TR 418
185/60 R14	82H	5.5J	190	578	8.6	475@ 2.45	-	267	-	TR413/TR 418
205/60 R13	87H	6.0J	211	575	8.3	545@ 2.45	-	266	-	TR413/TR 418
165/65 R13	77T	5.0J	167	545	8.5	412@ 2.45	-	252	-	TR413/TR 418
155/70 R13	75S	4.5	157	534	8.8	387@ 2.45	-	250	-	TR 13
175/80 R13	86S	5.0	177	610	8.8	530@ 2.45	-	274	-	TR 13
175/80 R14	88S	5.0	177	636	8.8	560@ 2.45	-	287	-	TR 13
165/70 R14	81S	5.0	170	588	8.6	462@ 2.45	-	-	-	-
165/80 R15	86T	4.5J	165	645	9.5	530@ 23.5	-	294	-	TR 13